



RHINO
Tough, Vibrant, Recoverable

The Toughest
Graphics
On Earth
PERIOD.



rhinopanel.com

Rhino Maintenance and Repair

Rhino Graphic Panels are fabricated with exterior grade materials. These materials require no regularly scheduled maintenance. However, cleaning & protective waxing of the panels will insure that your graphics remain vibrant and effective for many years and can refresh the lustre of the surface while hiding small scratches and scuffs.

Cleaning Rhino sign panels:

As with any sign, wind, rain and dust can dull your Rhino panels. To clean the surface, use hand grade soap and water. Rinse thoroughly. Dry the surface with a soft cloth or chamois.

Protection:

Aardvark Graphic Solutions recommends cleaning your signs as needed. When you clean your panels you can insure additional protection by applying any standard grade auto wax or sealant (see label for instructions). Applying wax or sealant can increase the life and appearance of your signs over time. The application of wax or sealant is not required by the warranty. Aardvark Graphic Solutions recommends this application every 2-3 years.

Vandalism:

Rhino panels are shatter and highly graffiti resistant. Vandalism can ruin any sign but only with Rhino panels can you repair knife cuts, gouges and burns. You can recover vandalism damage using the following techniques:

1. Spray paint, markers, small scratches and burns can be removed using a soft cloth with Isopropyl Alcohol. For more difficult markings and paints, use a soft cloth wet with V, M, & P naphtha or kerosene, followed immediately with a thorough cleaning with soap and water. 0000 Steel Wool can be used if there are any remaining scratches, followed by buffing the panels with auto grade wax or sealant. You must buff the entire sign when repairing a damaged area to even out the surface.

2. Gouges from knives, keys, or screw drivers can be sanded back with 600g sand paper, buffed with 0000 steel wool, then buffed with auto grade wax. If gouge filling is needed, Tape around repair area first then apply clear epoxy and scrape flat with a card, then follow the above steps to blend the area.

If you're not comfortable repairing your Rhino Panels, you can ship them to Aardvark Graphic Solutions and we will repair the panels for a nominal fee. As with any sign, repairs might be noticeable but usually the panel comes back to near new condition and save the purchase of a replacement panel.

Glazing compounds and masking adhesives can be removed from Rhino panels by using a soft cloth wet with V, M, & P naphtha or kerosene, followed immediately with a thorough cleaning with soap and water. Wash with a mild soap or detergent and water using as much water as possible during the process. Apply water to large areas with a soft bristle mop used in window washing and to smaller areas with a soft damp cloth, sponge or chamois. If it is necessary to dry the washed surface, use a clean damp chamois.

rhinopanel.com

Aardvark Graphic Solutions, Inc.

1400 S. Lipan St., Denver, CO 80223 Tel: 303-282-6695 Fax: 303-282-6698